

Cabinet Liner


Specifications



ORIGIN	China
SPECIES	Poplar
CORE	Poplar
FACE/BACK	HPL, Softwood Veneer
FINISH	White, Black
SIDES	1-Side, 2-Side
SIZE	48" x 96"
HPL THICKNESS	0.5mm
GLUE TYPE	Interior, TSCA Title VI
MOISTURE CONTENT	<12%
APPLICATIONS	Cabinet box construction, as well as casing and shelving



WHITE CABINET LINER	5.2MM	12MM	15MM	18MM
# OF PLYS	5	9	11	13
THICKNESS VARIATION	4.8mm-5.2mm	11.5mm-12.3mm	14.5mm-15.3mm	17.5mm-18.3mm
SHEETS PER CRATE	180	78	62	52
BLACK CABINET LINER		12MM		18MM
# OF PLYS		9		13
THICKNESS VARIATION		11.5mm-12.3mm		17.5mm-18.3mm
SHEETS PER CRATE		78		52



PER THE REQUIREMENTS OF THE ASTM E84-2022 STANDARD TEST METHOD FOR SURFACE BURNING CHARACTERISTICS OF BUILDING MATERIALS, THE CABINET LINER WE SOURCE HAS A FLAME SPREAD INDEX (FSI) OF 20 AND A SMOKE DEVELOPED INDEX (SDI) OF 25, GIVING THIS PRODUCT A CLASS A FIRE RATING.

A sampling of the Cabinet Liner USply sources was third-party tested following standard industry tests that include ASTM D3359-23 Rating Adhesion by Tape Test (crosshatch method), ANSI/KCMA A161.1-2022 Section 9.4 Chemical Resistance Test, and EN16611:2023 Furniture - Assessment of the Surface Resistance to Micro-Scratching Test. For actual test results, please contact your USply Sales Representative. USply does not guarantee results and assumes no obligation or liability related to this information. Test results are relevant only to the sample(s) tested.

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.