

Underlayment Specifications



Product Information

Specifically designed as flooring underlayment, the Underlayment we source is produced in Indonesia and is sustainably forested. Each sheet is calibrated and sanded on both sides, providing a smooth, flat surface for ideal installation.

Applications

This underlayment can be used under resilient flooring materials, such as vinyl and linoleum sheets and tiles, as well as under hardwood, laminate, and carpet. Backed by a one-year limited warranty, our plywood underlayment features a smooth surface, without voids from knots or other surface imperfections common with subflooring, ensuring the best possible results for a variety of approved flooring installations.



Origin	Species	Finish	Size	Core
Indonesia	Falcata	Raw, Front & Back	4'x8'	Falcata

Veneer Thickness	Thickness Tolerance	Surface Sanding	Glue Type	Moisture Content
1mm	4.6mm-5.2mm	240-320 grit finish; Calibrated; Sanded 2 sides	Melamine, TSCA Title VI / EPA (Carb)	<12%

Thickness	# of Plies	Sheets per Crate
5.2mm	3	210

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.

www.USply.net

US Office:

9400 NW 104th St., #100, Medley, FL 33178
Phone: (305) 722-6622, Email: info@usply.net