

# Premium Underlayment Specifications



## Product Information

Specifically designed as flooring underlayment, our Premium Underlayment is produced in Indonesia and features sustainably forested Natural Birch face and back with a combi core of Falcata and mixed light hardwood (MLH). Each sheet is calibrated and sanded on both sides, providing a smooth, flat surface for ideal installation.



## Applications

This underlayment can be used under resilient flooring materials, such as vinyl and linoleum sheets and tiles, as well as under hardwood, laminate, and carpet. Backed by a one-year limited warranty, our plywood underlayment features a smooth surface, without voids from knots or other surface imperfections common with subflooring, ensuring the best possible results for a variety of approved flooring installations.



Origin	Species	Finish	Size	Core
Indonesia	Natural Birch	Raw, Front & Back	4'x8'	Combi Core of Falcata and MHL

Veneer Thickness	Thickness Tolerance	Surface Sanding	Glue Type	Moisture Content
0.3mm	4.8mm-5.6mm	240-320 grit finish; Calibrated; Sanded 2 sides	Interior, Exterior, TSCA Title VI / EPA (Carb)	<12%

Thickness	# of Plies	Sheets per Crate
5.2mm	5	180

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.

[www.USply.net](http://www.USply.net)

### US Office:

5870 NW 163rd St., Miami Lakes, FL 33014  
Phone: (305) 722-6622, Fax: (305) 722-6623, Email: [info@usply.net](mailto:info@usply.net)

### Asia Office:

RM 1708, Fudibeicheng Center, No. 1165 Moganshan RD, Hangzhou, Zhejiang, P.R. China  
Phone: (0571) 8546-2500, Fax: (0571) 8546-2577