

# Indonesian Birch Specifications



## Product Information

Our Indonesian Birch is a rotary cut, plywood that has exceptional machining properties and is suitable for natural, colored, and painted finishes. With a whole-piece veneer face, this import plywood features a Falcata and mixed light hardwood (MLH) core. This lighter weight core is often preferred over other birch species when end product weight is a consideration. Available in both raw and prefinished panels, we source several thicknesses and grades to provide flexibility in meeting a variety of needs.

## Applications

White Birch is known for being a highly versatile wood with a wide variety of uses. It is a strong building material and is mostly used for interior applications that include, but are not limited to, cabinetry, furniture, desks, shelving, trim work, lamination, and general woodworking.



Origin	Species	Finish	Size	Grade	Core
Indonesia	White Birch	Raw, Prefinish	4'x8'	C2, C3, Shop	Falcata & MLH

Veneer Cut	Veneer Thickness	Surface Sanding	Glue Type	Moisture Content
Rotary Cut (R/C), WPF	0.3mm	240 - 320 grit finish	Interior, TSCA Title VI / EPA (Carb)	<12%

Thickness	# of Plies	Thickness Variation	Sheets Per Crate
5.2mm	5	4.8mm-5.2mm	180
12mm	9	11.5mm-12.3mm	78
18mm	13	17.5mm-18.3mm	52

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.

[www.USply.net](http://www.USply.net)

### US Office:

5870 NW 163rd St., Miami Lakes, FL 33014  
 Phone: (305) 722-6622, Fax: (305) 722-6623, Email: info@usply.net

### Asia Office:

RM 1708, Fudibeicheng Center, No. 1165 Moganshan RD, Hangzhou, Zhejiang, P.R. China  
 Phone: (0571) 8546-2500, Fax: (0571) 8546-2577