

# Euro Birch

## Specifications



<b>ORIGIN</b>	Russia
<b>SPECIES</b>	Birch
<b>CORE</b>	Birch
<b>FACE/BACK</b>	Birch
<b>GRADE</b>	B/BB, BB/BB, BB/CP
<b>FINISH</b>	Raw, Prefinish
<b>SIZE</b>	4' x 8', 5' x 5', 5' x 10'
<b>VENEER CUT</b>	Rotary Cut, WPF
<b>VENEER THICKNESS</b>	1.4mm
<b>SURFACE SANDING</b>	80-120 grit finish
<b>GLUE TYPE</b>	48" x 96", 60" x 120" (Exterior, Phenolic) 60" x 60" (Interior, TSCA Title VI)
<b>MOISTURE CONTENT</b>	<14%
<b>APPLICATIONS</b>	Cabinets, furniture, flooring, drawer sides, packaging, industrial components, toys, store fixtures, woodworking projects



THICKNESS	# OF PLYS	THICKNESS VARIATION	SHEETS PER CRATE
3mm	3	2.6mm-3.3mm	130
6mm	5	5.5mm-6.4mm	65
9mm	7	8.4mm-9.4mm	44
12mm	9	11.3mm-12.5mm	33
15mm	11	14.2mm-15.6mm	26
18mm	13	17.1mm-18.7mm	22
24mm	17	22.5mm-24mm	17



EURO BIRCH FOLLOWS ALL GUIDELINES PER GOST STANDARDS.

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.

# Euro Birch

## General Standards



STANDARD THICKNESS (MM)	NUMBER OF PLYS	SANDED PLYWOOD		NOT SANDED PLYWOOD	
		ULTIMATE THICKNESS TOLERANCE (MM)	THICKNESS VARIANCE (MM)	ULTIMATE THICKNESS TOLERANCE (MM)	THICKNESS VARIANCE (MM)
3	3	-0.3	0.6	-1.333333333	0.6
4	3	-0.3	0.6	-2	1
6,7	5	-0.4	0.6	-2.25	1
8,9	7	-0.4	0.6	-2	1
10,11,12	9	-0.5	0.6	-2.2	1
15	11	-0.7	0.6	-1.714285714	1.5
18	13	-0.7	0.6	-1.625	1.5
21	15	-0.8	0.6	-1.555555556	1.5
24	17	-0.9	0.6	-1.5	1.5
27	19	-0.833333333	1	-1.454545455	2
30	21	-0.846153846	1	-1.416666667	2
35	23	-0.866666667	1.2	-1.357142857	2.5
40	31	-0.875	1.2	-1.333333333	2.5

Based on availability, USply reserves the right to substitute product that may vary in species, core, country of origin, and/or other specifications.